


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	8/26/2015	RJC	JAG
2	16-0033	UPDATED TO NEW STANDARD. ADDED PART OF KIT NOTE. -7 CH'D DIM WAS Ø1.50 IS Ø1.50±.02. ADDED ENGRAVE P/N NOTE. -11 ADDED DIM 90°. CH'D MAT'L WAS 6061 IS 7075. -7 , -13 CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416 TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2.	2/15/2016	DPD	JAG
3	16-0201	-3 CH'D DIM WAS 5.572 IS 5.597. -11 CH'D DIM WAS 5.572 IS 5.597. -13 CH'D MATERIAL WAS 4140/4142 Q&T IS 4140/4142, ADDED HEAT TREAT RC 28-32.	10/31/2016	RJC	JAG






NOTE:
1. REF. AGUSTA T/N: 3G6405G12031.
2. PART OF KIT: RBW6405G11931-3G.

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	CUP	6061		2
			-3	1	TUBE	6061		3
			-5	1	WASHER	S.S.		4
			-7	1	PULL STUD	4140/4142		5
			-9	1	NUT	ALUMINUM BRONZE		6
			-11	2	HALF SET	7075		7
			-13	1	KNURLED SCREW	4140/4142		8
		B/O	-15	1	THIN NUT	STEEL	9/16-18 UNF (MCMASTER-CARR #93839A830)	1
		B/O	-17	1	THRUST BRG CAGE ASSY	STEEL	15mm I.D. X 28mm O.D. (MCMASTER-CARR #5909K13)	1
		B/O	-19	2	THRUST BRG. WASHER	STEEL	15mm I.D X 28mm O.D. (MCMASTER-CARR #5909K85)	1

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G	REV 3
MAT'L	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ±.5°
	.X ± .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
SCALE 1:6	DATE 8/20/2015
	SHEET 1 OF 8

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






SECTION A-A

(-1)
CUP

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-1	REV 3
MAT'L 6061	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH CLEAR ANODIZE	.XXX ± .005 FRACTIONS ± 1/8
SPEC MIL-A-8625, TYPE II, CLASS I	.XX ± .01 ANGLES ± .5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
SCALE 1:4	DATE 8/20/2015
	SHEET 2 OF 8

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0201	-3 CH'D DIM WAS 5.572 IS 5.597.	10/31/2016	RJC	JAG






SECTION B-B

③
TUBE

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-3	REV 3
MAT'L 6061	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH CLEAR ANODIZE	.XXX ± .005 FRACTIONS ± 1/8
SPEC MIL-A-8625, TYPE II, CLASS I	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
SCALE 1:2	DATE 8/20/2015
	SHEET 3 OF 8

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED




(-5)

WASHER

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-5	REV 3
MAT'L S.S.	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± .5°
	.X ± .1 SURFACES = 125°
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
SCALE 1:1	DATE 8/20/2015
	SHEET 4 OF 8

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0033	-7 CH'D DIM WAS Ø1.50 IS Ø1.50±.02. ADDED ENGRAVE P/N NOTE. CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416 TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2.	2/15/2016	DPD	JAG






(-7)

PULL STUD

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-7	REV 3
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 34-38	DIMENSIONS ARE IN INCHES
FINISH ZINC PLATE	.XXX ± .005 FRACTIONS ± 1/8
SPEC ASTM B633 TYPE I SC 2	.XX ± .01 ANGLES ± .5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 8/20/2015	USED ON MODEL
SHEET 5 OF 8	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






⑨
NUT

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-9	REV 3
MAT'L ALUMINUM BRONZE	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± .5°
	.X ± .1 SURFACES = 125°
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
SCALE 1:1	DATE 8/20/2015
	SHEET 6 OF 8

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0033	-11 ADDED DIM 90°. CH'D MAT'L WAS 6061 IS 7075.	2/15/2016	DPD	JAG
3	16-0201	-11 CH'D DIM WAS 5.572 IS 5.597.	10/31/2016	RJC	JAG




SECTION C-C

(-11)
HALF SET




DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-11	REV 3
MAT'L 7075	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH CLEAR ANODIZE	.XXX ± .005 FRACTIONS ± 1/8
SPEC MIL-A-8625, TYPE II, CLASS I	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:2	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 8/20/2015	USED ON MODEL
SHEET 7 OF 8	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0033	-13 CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416 TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2.	2/15/2016	DPD	JAG
3	16-0201	-13 CH'D MATERIAL WAS 4140/4142 Q&T IS 4140/4142, ADDED HEAT TREAT RC 28-32.	10/31/2016	RJC	JAG



SECTION D-D



(-13)

KNURLED SCREW

DART AEROSPACE	
TITLE TOOL, T/R SLIDER BUSHING REMOVAL (NEW STYLE BUSHING)	
DWG NO. RBW6405G12031-3G-13	REV 3
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 28-32	DIMENSIONS ARE IN INCHES
FINISH ZINC PLATE	.XXX \pm .005 FRACTIONS \pm 1/8
SPEC ASTM B633 TYPE I SC 2	.XX \pm .01 ANGLES \pm 5°
DRAWN BY: CLOUGH	.X \pm .1 SURFACES = 125
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 8/20/2015	USED ON MODEL
SHEET 8 OF 8	